

I33 MEDIUM DUTY CASTERS

※ WHEEL MATERIAL

- TPR — THERMOPLASTIC RUBBER ON PP CORE
- PPU — POLYURETHANE ON PP CORE
- BR — BLACK RUBBER
- WO — WITHOUT THREAD GUARDS
- CONYFRP — BROWN NYLON FIBER

※ HOUSE MATERIAL

- STEEL ZINC PLATED
- STAINLESS STEEL

※ BRAKE OPTIONS

- TL — TOTAL LOCK
- SL — SINGLE LOCK

※ DOUBLE BEARING RACEWAYS

※ TEMPERATURE RANGE (ONLY FOR BROWN NYLON FIBER)

- -20 C ~ 250 C FOR STEAM / MOIST HEAT ENVIRONMENTS

※ STEM OPTIONS

- P — PLATE
- TS — THREADED STEM
- GR — GRIP RING
- BH — BOLT HOLE

※ TOP PLATE



CONYFRP

Diameter (mm)(inch)		SWIVEL (mm)			FIXED (mm)	
75 (3")	95 x 64	74 x 45		96 x 67		74 x 45
100 (4")	95 x 64	74 x 45		96 x 67		74 x 45
	105 x 79	80 x 60		106 x 80		80 x 60
125 (5")	95 x 64	74 x 45		96 x 67		74 x 45

Diameter (mm)(inch)	Tread Width (mm)	Load (kgs)	Load Height (mm)	Material	SWIVEL No.	FIXED No.	BEARING TYPE
75 (3")	32	90	109	TPR	I33S3P-TPRB-WO	I33F3P-TPRB-WO	BEARING
100 (4")	32	115	132	TPR	I33S4P-TPRB-WO	I33F4P-TPRB-WO	BEARING
	37	125	133	BROWN NYLON FIBER	I33S4P-112- CONYFRP-105X79	X	PLAIN
125 (5")	32	135	156	TPR	I33S5P-TPRB-WO	I33F5P-TPRB-WO	BEARING